



UPS GLOBAL Series

ON LINE DOUBLE CONVERSION

Key points:

*GLOBAL is fit for any market application;
It ensures always high performance;
It offers all the communication interface you might need;
It features Hot Swap batteries;
It has low recharge time;
Its autonomy can be expanded with battery packs;
It has a wide range of available customizations.*



TECHNOLOGY

GLOBAL ensures a clean and an uninterrupted output, independently on the conditions of the mains. The UPS on the GLOBAL series are double conversion On Line UPS, classified as VFI-SS-111, according to EN 62040-3 European Norm.

EFFICIENT

The extreme quality of the components and technical solutions used while designed GLOBAL, make it the best answer to all your continuity needs in demanding environments, where quality comes first. Its high efficiency makes you save power and is recognized as an energy-saving product by various national regulations. The UPS of the GLOBAL series also offer the High Efficiency Mode to have minimum power consumption when the On Line technology is not necessary.

CONNECTION

The UPS of the GLOBAL series offers all the connections you might need: different output groups, communication ports and software management. In specific, the GLOBAL features a USB port, a Smart Slot to connect SNMP and AS400 boards, two separate and programmable output groups. Besides, all the UPS of the GLOBAL series have the Emergency Power Off contact, which allows their use in environments where a high safety level is necessary. These UPS can also be equipped with an external manual By Pass.

HOT SWAP BATTERIES

We designed the GLOBAL to make as easy as possible the replacement of the batteries. You can remove the battery module through the frontal panel without having to interrupt the operation of the UPS and the loads connected to it.

EXTRA AUTONOMY

You can expand the autonomy of the GLOBAL for how long you need to the external battery packs. You can also reduce the recharge time adding an additional battery charger to the battery packs.

UPS GLOBAL Series

ON LINE DOUBLE CONVERSION

CUSTOMIZATIONS

Tropicalization
 REM
 CEI016
 Frequency Converter

ACCESSORIES

Internal network board (SNMP)
 Dry contacts board (AS400)
 External By Pass
 Enviromental and safety sensors/modem
 RS 485 contact board
 Isolation Transformer Kit (external box)

Model		GLOBAL 20	GLOBAL 30	GLOBAL 40	GLOBAL 60
Power (VA/W)		1000/700	1500/1050	2000/1400	3000/2100
Connections	INPUT	Cable with IEC 10 A to schuko plug			Cable with IEC 16 A to shuko plug
	OUTPUT	2 + 2 x IEC 10 A programmable		4 + 4 x IEC 10 A programmable, 1 x IEC 16 A	
Interface	Communication	RS232 & free contacts + USB (when in use it disabile RS 232)			
	Display	LCD			
	EPO	YES, Emergency power OFF "NC"			
Regulations		EN 62040-1 / EN 62040-2 / EN 62040-3			
Size (WxDxH) mm		152 x 420 x 238		225 x 425 x 360	
Weight (net / gross) kg		16,2/17,7	17/18,5	28/30	33/35

Onpower reserves the right to implement changes without prior notice

